



# 1506 Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2</sup>™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



## CONFIGURATIONS



**1506**  
Standard



**1506WF**  
With Foam



**1506NF**  
No Foam



**1506TP**  
With TrekPak Divider System

## DIMENSIONS

<b>Interior (LxWxD)</b>	18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm)
<b>Exterior (LxWxD)</b>	20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)
<b>Lid Depth</b>	2.00" (5.1 cm)
<b>Bottom Depth</b>	5.80" (14.7 cm)
<b>Total Depth</b>	7.8" (19.8 cm)
<b>Int Volume</b>	0.79 ft <sup>3</sup> (0.022 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

## MATERIALS

<b>Body</b>	Proprietary Polypropylene Blend
<b>Latch</b>	ABS
<b>O-Ring</b>	EPDM
<b>Purge Body</b>	ABS

**Purge Vent**

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

---

■ Black

WEIGHT

---

<b>Weight With Foam</b>	6.30 lbs (2.9 kg)
<b>Weight Empty</b>	5.35 lbs (2.4 kg)
<b>Buoyancy</b>	51.69 lbs (23.4 kg)


TEMPERATURE

---

<b>Minimum Temperature</b>	-60°F (-51.1 °C)
<b>Maximum Temperature</b>	160°F (71.1 °C)

ACCESSORIES

---



**1506AirFS**  
4 pc. Replacement Foam Set

---