

1630 Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• 4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)

- Watertight, crushproof, and dustproof

3 level Pick N Pluck[™] with convoluted lid foam
Automatic pressure equalization valve - balances interior pressure, keeps water out

- · Easy open double-throw latches
- Fold down handles
- Note: Please consult a sales specialist for more details.
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Reinforced corners
- Retractable extension trolley handle
- Stackable
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law

CONFIGURATIONS



1630 Standard



1634 With Padded Dividers



1630NF No Foam



1630WF With Foam

DIMENSIONS

| Interior (L×W×D) | 27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm) |
|-----------------------|--|
| Exterior (L×W×D) | 31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm) |
| Lid Depth | 3.25" (8.3 cm) |
| Bottom Depth | 12.14" (30.8 cm) |
| Total Depth | 15.39" (39.1 cm) |
| Int Volume | 5.21 ft ³ (0.148 m ³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

Body





| Latch | ABS |
|------------|--------------------------------|
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

Black

WEIGHT

| Weight With Foam | 36.00 lbs (16.3 kg) |
|--------------------|-----------------------|
| Weight Empty | 31.00 lbs (14.1 kg) |
| Buoyancy | 350.00 lbs (158.8 kg) |
| Master Pack Weight | 42.00 lbs (19.1 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67 Def Stan 81-41

OTHER

| Wheels | 4 |
|-------------------|-----|
| Extendable Handle | yes |
| Master Pack | 1 |
| Nameplate | yes |
| Reduced Area | yes |

ACCESSORIES



1631 5 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1633 Replacement O-ring



1506TSA TSA Lock



1635 Padded Divider Set



1500D Desiccant Silica Gel



1639 Lid Organizer



1630DC Document Container Accessory

AVT Verpatec AG Haselholzstrasse 5 CH-8732 Neuhaus