



1780

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **The new class of XXL Peli Transport Cases**
- **Watertight, crushproof, and dustproof**
- 50/50 lid-to-base ratio for easy loading
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Completely detachable lid for full access
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1780
Standard



1780NF
No Foam



1780WF
With Foam

DIMENSIONS

Interior (LxWxD)	41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm)
Exterior (LxWxD)	44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm)
Lid Depth	7.58" (19.3 cm)
Bottom Depth	7.30" (18.5 cm)
Total Depth	14.88" (37.8 cm)
Int Volume	7.63 ft ³ (0.216 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer

Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	49.00 lbs (22.2 kg)
Weight Empty	38.40 lbs (17.4 kg)
Buoyancy	500.00 lbs (226.8 kg)
Master Pack Weight	56.00 lbs (25.4 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

Def Stan 81-41

OTHER

Wheels	4
Master Pack	1
Nameplate	yes

ACCESSORIES



1781
6 pc. Replacement Foam Set



1783
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel